

## Sewing Kit Instructions

Our sewing kit is designed to help you securely attach your replacement jute sling to the frame of your raised dog bed. Keeping the sling tightly fitted to the frame is the easiest way to maintain your bed and keep it in great condition.

### **Kit Includes:**

- 1 heavy-duty needle
- 2.5 metres of jute twine

### **How to Attach the Replacement Sling**

Prepare the Sling - Cut two small holes (approximately 10 mm) in the bottom corners of the closed end of the sling/cover.

Fit the Sling to the Frame - Slide the sling over the frame, pushing the bed legs through the holes you have cut. The holes may appear small, but the jute will stretch slightly.

Position the Sling - Fold the excess material inside itself until it sits evenly along the cross arm of the frame when pulled tight.

Start Stitching - Begin stitching from the side of the cover as close as possible to the leg. Push the needle through one side of the cover, bring it around the frame, and push it through the other side.

Tighten the Sling - Use the needle against the cross arm as a lever to pull the cover tight while stitching.

Continue Sewing - Place stitches approximately 4-6 cm apart and continue across the frame until you reach the other side.

Finish the Stitching - Add an extra stitch at the end for strength. Loop the twine around the needle to form a knot, pull tight, and cut the excess twine.

Final Knot - Remove the needle and tie a double knot to secure the stitching.

Following these steps will ensure the sling is firmly attached and help keep your raised dog bed in tip-top condition for longer.

